

Name: _____
 Date: _____
 Track: _____

Track Conditions

Size: Open Med. Tight
 Traction: High Med. Low
 Surface: Smooth Med. Bumpy

Front suspension

Camber angle _____ °
 Track width _____ mm
 Ride height _____ mm
 Caster angle _____ mm
 Toe angle _____ °
 Rebound stop _____ mm
 Bump stop None Use
 Lower arm spacer _____ mm
 Upper arm position _____ mm
 Anti-roll bar _____ mm

Front shock

Piston _____
 Oil # _____
 Springs _____
 Shock position

Steering ackerman

A
 B
 C
 D

Rear suspension

Body mount arm _____ mm
 Camber angle _____ °
 Track width _____ mm
 Ride height _____ mm
 Upright spacer _____ mm
 Rebound stop _____ mm
 Lower arm position(H0134) 4.5mm 5.5mm 6.5mm
 Anti-roll bar Wire _____ mm
 Adjustable _____ mm

Rear shock

Piston _____
 Oil # _____
 Springs _____
 Shock position

Body mount arm Long (H0466C)
 Short (H0466D)

Engine

Type _____
 Gasket _____ mm Muffler _____
 Plug _____ Fuel _____

Clutch

Clutch shoe Black Gray Red
 Centrifugal shoe _____
 Spring _____
 Clutch bell clearance _____ mm
 Spring adj. nut position _____ mm

Tire

<Front>

Type _____
 Dia.(start) L / R
 Dia.(finish) L / R

<Rear>

Type _____
 Dia.(start) L / R
 Dia.(finish) L / R

Brake pad

Black Yellow

Body

Type _____
 Body position _____ mm
 Rear spoiler _____ mm

Drive ratio

Gear ratio _____ Side pulley
 1st. _____ 25T
 2nd. _____ 26T

Result

Race time / Lap _____
 Best lap (1Lap) _____

Comments:

.....

