

Name: _____
Date: _____
Track: _____

Track Conditions

Size: Open Med. Tight
Traction: High Med. Low
Surface: Smooth Med. Bumpy

Front suspension

Camber angle _____ °
Track width _____ mm
Ride height _____ mm
Camber angle _____ °
Caster angle _____ mm
Toe angle _____ °
Rebound stop _____ mm
Bump stop None Use
Lower arm spacer _____ mm
Upper arm position _____ mm
Anti-roll bar _____ mm

Front shock

Piston _____
Oil # _____
Springs _____
Shock position

Steering ackerman

A
 B
 C
 D

Rear suspension

Body mount arm _____ mm
Camber angle _____ °
Track width _____ mm
Ride height _____ mm
Camber angle _____ °
Toe angle _____ °
Rebound stop _____ mm
Bump stop None Use
Lower arm position(H0134) 4.5mm 5.5mm 6.5mm
Upright spacer _____ mm
Anti-roll bar Wire _____ mm
 Adjustable _____ mm

Rear shock

Piston _____
Oil # _____
Springs _____
Shock position

Body mount arm Long (H0466C)
 Short (H0466D)

Engine

Type _____
Gasket _____ mm Muffler _____
Plug _____ Fuel _____

Clutch

Clutch shoe Black Gray Red
Centrifugal shoe _____
Spring _____
Clutch bell clearance _____ mm
Spring adj. nut position _____ mm

Tire

<Front>	<Rear>
Type _____	Type _____
Dia.(start) <u> L </u> / <u> R </u>	Dia.(start) <u> L </u> / <u> R </u>
Dia.(finish) <u> L </u> / <u> R </u>	Dia.(finish) <u> L </u> / <u> R </u>

Brake pad

Black Yellow

Body

Type _____
Body position _____ mm
Rear spoiler _____ mm

Drive ratio

Gear ratio _____ Side pulley
1st. _____ 25T
2nd. _____ 26T

Result

Race time / Lap _____
Best lap (1Lap) _____

Comments:

.....
.....
.....
.....